

Model S0560

Recessed, Wall Mounted,
Swing Down Eye/Face Wash



SPECIFICATIONS:

Model S0560 is a recessed, wall mounted swing down eye/face wash that is installed in the wall with a stainless steel cabinet and ABS plastic eye/face wash spray heads. The eye/face wash swings down horizontally and the water flow is activated automatically. The eye/face wash flow is terminated once the unit has been swung back up into the cabinet for storage.

NOTE: Unit is ADA compliant when installed at the appropriate height.

STANDARD EQUIPMENT:

Spray Head Assembly: ABS yellow plastic eye/face wash heads with integral flip dust covers, internal flow controls and filters to remove debris from the water.

Valve: Swing down valve is mounted in the cabinet on the wall and has a 50 mesh inline strainer.

Water Supply: 1/2" NPT female threaded brass inlet.

Mounting: Wall mounted, 18 gage stainless steel cabinet.

Universal Sign: ANSI compliant, vertical identification sign.

Weekly Test Tag: A water proof test card to record the date and inspector's name for weekly functional testing of the unit.

Model: S0560



OPTIONAL ACCESSORIES:

Additional costs may be incurred

- AL3 Electric alarm for recessed laboratory application
- FLW2 Flow switch, single pole
- PAN Waste water drain pan
- SDC Stainless steel dust covers
- TMB1 Thermostatic mixing valve with an external cold water bypass that delivers tepid water as outlined by ANSI Z358.1-2004
- TMV1 Thermostatic mixing valve that delivers tepid water as outlined by ANSI Z358.1-2004

Acorn Safety assumes no responsibility for use of void or suspended data. © Copyright 2007 Acorn Safety, City of Industry, CA, A Division of Acorn Engineering Company. Please visit www.acornsafety.com for most current specifications.

Submittal # **S0560**
[Cat. 07/EFW] Rev. A 2/17/09

Product carries the following certifications:



Test rating conditions are compliant to ANSI Z358.1-2004



Member of Acorn
Family of Companies

ACORN SAFETY
15125 Proctor Avenue
City of Industry, CA
91746 U.S.A.
Phone 800-591-9372
626-855-4804
Fax 626-937-4213
www.acornsafety.com

